

VALVE LIFT TIMING(1mm-1mm) ANIMA-4V



MARK	PN#	TYPE	
DT190-2	86878	High-RPM	Camshaft for FSM/FDX/SYS/FLX/GP5 etc
DT190-3	87163	High-RPM	Camshaft for 150/160cc
DT190-4	87347	Low-Mid RPM	Camshaft for 190FE/190FD/190FZ5

DT190-2 (#86878)	
INT OPEN[deg]	EXH OPEN[deg]
BTDC 18	BBDC 42
INT CLOSE[deg]	EXH CLOSE[deg]
ABDC 42	ATDC 18
TOTAL DURATION[deg]	240
LOB CENTER[deg]	102
MAX LIFT[mm]	7.2
OVERLAP[deg]	36

DT190-3 (#87163)	
INT OPEN[deg]	EXH OPEN[deg]
BTDC 24	BBDC 36
INT CLOSE[deg]	EXH CLOSE[deg]
ABDC 36	ATDC 24
TOTAL DURATION[deg]	240
LOB CENTER[deg]	96
MAX LIFT[mm]	7.2
OVERLAP[deg]	48

DT190-4 (#87347)	
INT OPEN[deg]	EXH OPEN[deg]
BTDC 0	BBDC 40
INT CLOSE[deg]	EXH CLOSE[deg]
ABDC 40	ATDC 0
TOTAL DURATION[deg]	220
LOB CENTER[deg]	110
MAX LIFT[mm]	6.3
OVERLAP[deg]	0

※※RECOMMEND VALVE CLEARANCE: 0.08±0.03※※

